

7.0 BID PROPOSAL

Bid # 5674, 2-Yard Dump Bodies

7.1 UNIT DESCRIPTION – for 60" CA Cab/Chassis

Make RUGBY	Model DU-9-3	Year 2002
-------------------	---------------------	------------------

7.2

60"CA	BASE PRICE, as specified, per unit	\$ 9200⁰⁰
--------------	------------------------------------	-----------------------------

7.3 OPTIONAL UNIT – same basic specification, except CA spec

**model DU-11-3
4R 2002**

Box for 84" CA Cab/Chassis	\$ 9600⁰⁰
----------------------------	-----------------------------

8.0 FREIGHT TERMS

FOB destination, freight prepaid. All freight charges must be included in bid pricing.

9.0 DELIVERY

Delivery will occur **45** days after proper notification of bid award.

10.0 CONTRACTOR'S STATEMENT

I have read and fully understand all the conditions, specifications, and special instructions herein set forth above in paragraphs 1.0 through 9.0. I hereby agree to comply with all said conditions, special instructions, and specifications as stated or implied.

Signature: Robert H. Abel	Title: GM
Print Name: Robert H. ABEL	
Company: FRONTIER TRUCK EQ	Date: 2-8-02
Street: 7167 E. 53RD PLACE	Phone #: 303-284-4311
City/State/Zip: COMMERCE CITY, CO 80022	Fax #: 303-286-7188

6.0 SPECIFICATIONS

6.1 Equipment bid on this proposal must meet or exceed the following minimum requirements. Any exceptions must be noted and listed on a separate sheet.

2-YARD DUMP BODIES

GENERAL: The following specifications describe a two-yard dump body to be mounted on a one-ton cab/chassis with a cab/axle of 60" to be purchased separately. Successful dump body vendor will be responsible for delivery of completed unit to City of Fort Collins, 835 Wood Street, Fort Collins. Bid price should reflect any delivery charge to the above. Cab/chassis will be delivered to body vendor by successful cab/chassis bidder or the City. A complete and up-to-date manufacturer's specification must accompany bid.

No.	Item	Description	Meets Spec?
6.2	QUANTITY:	One-Five (1-5)	
6.3	BODY:	2 cubic yard capacity, 8 ft. long x 6 ^{94"} 1/2 ft. wide. 10 gauge steel throughout with 3/4" oak or apitong between 10 gauge steel overlay, <u>water tight weld all around.</u> 2" taper at rear of floor. Side board pockets. Double-acting tail gate with manual release and 3/8" high strength steel chain.	Yes ___ No <input checked="" type="checkbox"/>
6.4	HOIST:	Class B TBEA telescopic, twin arm, or combo hoist. NTEA CLASS 20 8.6 TON	Yes ___ No <input checked="" type="checkbox"/>
6.5	UNDERCARRIAGE:	Longitudinal channel with interlaced or stacked cross member construction.	Yes <input checked="" type="checkbox"/> No ___
6.6	HYDRAULIC PUMP:	Engine-mounted, belt-driven hydraulic pump PTO driven pump is not acceptable	Yes <input checked="" type="checkbox"/> No ___
6.7	HYDRAULIC TANK:	Manual shut-off valve must be installed between hydraulic tank and hydraulic pump.	Yes <input checked="" type="checkbox"/> No ___
6.8	SAFETY LEG:	Drop-down "pogo-stick" type safety device with parallel lock-up position when not in use.	Yes <input checked="" type="checkbox"/> No ___
6.9	CAB SHIELD:	Half-cab shield with cut-out panel for rear vision.	Yes <input checked="" type="checkbox"/> No ___
6.10	LIGHTS:	- All lights must be rubber mounted, sealed assemblies with wiring run in conduit. - Stop lights recessed in rear - Tail lights recessed in rear - Backup lights recessed in rear Identification lights and reflectors must meet all State and Federal requirements	Yes <input checked="" type="checkbox"/> No ___

* Can NOT GUARANTEE WATER TIGHT
THERE IS NO WAY TO TEST FOR WATER TIGHT

No.	Item	Description	Meets Spec?
6.11	COLOR:	Black	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
6.12	BACK-UP ALARM:	Electronic, located so as to prevent damage from dumping or backing.	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
6.13	MUD FLAPS:	Swing mounted, approximately 24" x 30".	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
6.14	REAR HITCH:	<ul style="list-style-type: none"> - Combo pintle / 2" ball hitch capable of towing up to 14,000lbs. - Pintle hitch height specified at time of order - Heavy duty safety chain loops - 6-way electrical receptacle (female) for trailer towing must be STANDARD TCP-61-F or COLE - HERSEE 1235, or equal. Receptacle model as listed is very important. If questions exist regarding this receptacle model, please contact City (Fleet Services) prior to installation 	Yes <input type="checkbox"/> No <input type="checkbox"/>
6.15	WARRANTY:	One (1) year warranty commencing from date of delivery. Warranty shall cover defective components and workmanship and coverage shall include parts and labor associated with any defects. XXXXXXXXXX	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
6.16	GVW CERTIFICATION AND MSO:	Must be furnished at time of delivery <i>Dealer To Supply</i>	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
6.17	F. O. B. POINT	Delivery of completed unit shall be made to the Fleet Services facility at 835 Wood Street, Fort Collins	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
6.18	MANUALS:	Completed units must be delivered with operation, maintenance, and parts manuals for the hydraulic system.	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>