



Prepared For:
Rick Jordan
City Of Fort Collins Parks Division
Fort Collins CO

phone: (970) 221-6240
rjordan@fcgov.com

Dealer Information
RON'S EQUIPMENT COMPANY, INC., (AG)
906 NORTH HWY 287
CO 80524

Prepared By:
Jordan Radach
jordann@ronsequipment.com
mobile: 970-219-8331
Quote Date: 08/29/17
Valid Until: 09/27/17
Quotation Reference: 167292

Model: 260 T4

Qty: 1

Stock Order/Serial No: 2503291

JCB 260 TIER 4 FINAL WHEELED, VERTICAL LIFT, NEW GENERATION, SKID STEER LOADER
12 X 16.5 10PR HD Wide Track Tires and Wheels (provides 71.7" width)
ENCLOSED CAB PACKAGE - INCLUDES A/C, HEATER, VINYL SEAT, REVERSE ALARM, HYDRAULIC LOADER ARM FLOAT AND MANUAL LOCK QUICKHITCH
JCB CONTROLS WITH 7 WAY JOYSTICKS AND ATTACHMENT HARNESS (REQUIRED WITH HIGH FLOW)
NO BUCKET OPTION
NORTH AMERICA LANGUAGE PACK - CAB
STANDARD AUXILIARY HYDRAULICS - 24GPM AT 3335 PSI (87.1 LPM /230 BAR)
Cloth Air Suspension Seat (upgrade of deluxe vinyl air suspension seat)
Radio with Speakers and Aerial
Engine Block Heater- 110V
2 SPEED - WHEELED MACHINES
ELECTRIC QUICKHITCH
FOOT THROTTLE
PARALLEL LIFT ON VERTICAL LIFT MODELS - 260, 280 AND 260T
ISO AND DUAL HAND CONTROL PATTERN

Equipment Total 41,760.94

Total Customer Sale Price 41,760.94

Optional Extras (Optional Extras are not included in the totals)

MDS 84" Bucket 2,200.00
Work Saver 48" Pallet Forks 4,400 lb 795.00
78" Low Profile Bucket 1,748.00

Handwritten:
2,200.00 ✓
795.00 ✓
1,748.00 ✓
44,303.94

Notes: NJPA Contract #042815-JCB

2017 Q3 Pricing

Customer Acceptance: _____ Date _____

Dealer _____ Date _____





Features and Benefits

Standard Equipment and Features & Benefits related to this product are subject to change without notice

4.4L JCB EcoMAX TCAE-55 engine

No need for after treatment or regeneration due to HP being below 74 HP threshold for emissions

Servo Controls with hydrostatic transmission. Optional Creep Speed

Multiple speeds to accommodate variety of applications. Optional two speed with travel Speeds of 6.8 to 12.4 mph in both forward and reverse.

Machine braking provided through the hydrostatic transmission

Less wear parts and fail safe when engine is off

SAE certified ROPS/FOPS, left side entry

Safest skid steer on the market with side door entry

Meets IP69 water ingress standard

Protects worklights - 2 Front and 1 Rear, Reverse Alarm, Horn, and 12V Accessory Socket

24gpm @ 3335psi standard flow.
Optional 33gpm

Provides versatility of attachments and applications

Rated Operating Capacity of 2600 lbs, Vertical Lift Loader Design

Provides for maximum loader lift breakout force for superior digging performance

Choice of Standard Mechanical or Optional Powered Quick Hitch

Variety accommodates all users in a variety of applications

Cab tilts forward

Provide further access to the hydraulic components





Standard Equipment

Standard Equipment and Features & Benefits related to this product are subject to change without notice

ENGINE	4.4L (268 CID) 74 SAE Gross HP, JCB EcoMAX engine, centrifugal dry type dual stage air cleaner; Fuel filter with water separator; 1000 CCA battery; variable speed hydraulically driven fan.
TRANSMISSION	Servo Controls with hydrostatic transmission. Travel Speeds of 0-6.8 mph in both forward and reverse. Optional Creep speed provides operation from 0-1/2 of full speed for special applications. An optional two speed transmission is available providing a low range of 0-6.8 mph and a high range of 0-12.4 mph.
TIRES: FRONT and REAR	12 x 16.5 10 PR, Heavy Duty Wide Track JCB Tires providing 72 in width.
BRAKES	Machine braking provided through the hydrostatic transmission. Parking brake consists of multiple disc, oil immersed, spring applied hydraulic release that provides a fail safe with the engine off. Electrically activated through a switch on the instrument panel or by raising seat bar.
ELECTRICAL	Meets IP69 (external) IP67 (internal) water ingress standard. Worklights, 2 Front and 1 Rear, Reverse Alarm, Horn, and 12 volt Accessory Socket.
INSTRUMENTS	Audible and visual warning systems, right and left side mounted instrument panels. Standard electronic throttle control with optional foot throttle.
CAB OR CANOPY	SAE certified ROPS/FOPS, left side entry. Vinyl seat with seatbelt and operator restraint interlock for drive and loader functions. Cab units are pressurized and available with heat or heat and A/C, sliding left window and full side door. Right Hand glass standard on canopy and cab builds.
HYDRAULICS	24 gpm at 3335 psi standard flow. Optional 33 gpm at 3335 psi available.
LOADER	Rated Operating Capacity of 2600 lbs, Vertical Lift Loader Design provides vertical lift path and increased reach at full lift vs Radial Lift Designs. Auxiliary circuit is standard for operation of hydraulic powered attachments. Choice of Standard Mechanical or Optional Electric Quick Hitch. Hydraulic Float standard on all models. Loader Options include: Parallel Lift in raise only, SRS (smooth ride system), left hand auxiliary pipework.
SERVICEABILITY	Cab tilts forward to provide further access to the hydraulic components. Rear door provides class leading access to engine bay and daily maintenance and check points.





Product Quotation

**Prepared For:
Rick Jordan**

**City Of Fort Collins Parks Division
Fort Collins CO**



**Prepared By:
Jordan Radach
RON'S EQUIPMENT COMPANY, INC., (AG)
mobile:970-219-8331**

Image is for indicative purpose only and may not represent exact equipment being quoted